

PREPRINTING EQUIPMENT



Autoprimer



Stazione di primerizzazione automatica con termopressa



Automatic primer station with integrated heatpress





Autoprimer è una stazione di primerizzazione innovativa dotata di ugelli di precisione per primerizzare il tessuto in pochi secondi e uniformemente dal primo all'ultimo capo trattato.

Per ridurre gli sprechi è possibile impostare l'area da primerizzare sul display touch screen.

Autoprimer è disponibile in 2 taglie con piano di appoggio massimo di 600x400mm e 900x1500mm.

Autoprimer ospita due contenitori per il primer da 18 litri che possono essere usati per primerizzare tipi di tessuti diversi con il passaggio da un liquido all'altro estremamente semplice e veloce. Il circuito del primer in pressione assicura l'assenza di bolle d'aria.

Gli Autoprimer più piccoli possono essere forniti compresi di termopressa integrata con temperatura e durata della pressatura regolabili, così da adattarsi ad ogni tessuto.

Un sistema automatico cambia la carta tra la termopressa ed il tessuto per evitare che residui di primer sulla pressa possano macchiare il tessuto.

Dopo l'utilizzo, il sistema di lavaggio automatico permette in pochi minuti di lavare completamente il circuito e gli ugelli evitando che il primer possa ostruirli.



Autoprimer is an innovative priming station equipped with precision nozzles to prime the fabric in a few seconds and evenly from the first to the last treated item.

To reduce waste, you can set the area to be primed on the touch screen display.

Autoprimer is available in 2 sizes with a maximum working area of 600x400mm and 900x1500mm.

Autoprimer can accommodate two 18 liters primer containers that can be used to primer different types of fabrics, the transition from one liquid to another is extremely simple and fast. The pressurized primer circuit ensures the absence of air bubbles.

The smaller Autoprimer can be supplied with an integrated heat press with adjustable temperature and pressing time, so as to adapt to any fabric.

An automatic system changes the paper between the heat press and the fabric to prevent primer residues on the press from staining the fabric.

After use, the automatic washing system allows the circuit and nozzles to be completely washed in a few minutes, preventing the primer from obstructing them.



optional heatpress

	Autoprimer	Autoprimer BIG
Working area / Area primerizzazione	600x400mm	900x1500mm
Primer container / Serbatoio primer	18L	
Water container / Serbatoio acqua	9L	
Power supply / Alimentazione	230V 1Kw	
Pneumatic supply / Alimentazione pneumatica	6bar	
With heatpress / Con termopressa		
Power supply / Alimentazione	230V 3Kw	
Max. temperature / Temperatura massima	170°C	



Ser.Tec. Srl
Via Emilio Salgari 14/d - 31056 Roncade (TV) - Italy
Phone +39 (0)422 798184 - Fax. +39 (0)422 799711
e-mail: sales@ser-tec.org - Website: ser-tec.org

www.facebook.com/sertecsr
 www.twitter.com/sertecsr

Ser.Tec. reserves the right to make changes in specifications, materials and accessories without notice.
The result may differ from the information in this brochure.



Scan the QR code and watch the video of Autoprimer