

AUTOMATIC ROTOPRESS



ROTOPRESS

 Pressa pneumatica-automatica

Pneumatic-automatic heat press 



Rotopress:

Termopressa pneumatica doppia con quattro tavole girevoli automatiche e due teste riscaldanti. Grazie alle due teste, consente di trasferire i supporti in metà del tempo, raddoppiando così la produzione oraria insieme al posizionamento facilitato dei laser. Inoltre, consente la simultanea operatività di due operatori con mansioni differenti.

Optional: Diversi piatti con dimensioni differenti

Funzioni: Impostazione temperatura, impostazione tempi, regolazione pressione



Rotopress:

Double pneumatic heatpress with four automatic rotating tables and two heating heads. Thanks to the two heads, it allows transferring supports in half the time, doubling the hourly production along with the facilitated positioning of lasers. Additionally, it enables two operators to work simultaneously on different tasks.

Optional: Various plates with different sizes.

Functions: Temperature setting, time setting, pressure adjustment.



	ROTOPRESS
Dimensione piatto	50 x 40 cm
Massima temperatura	210 °C
Consumo	6 KW
Alimentazione	230V 50Hz
Alimentazione Pneumatica	6 Bar
Peso	300 kg
Hz	50/60 Hz

	ROTOPRESS
Platen size	50 x 40 cm
Max. temperature	210 °C
Consumption	6 KW
Power supply	230V 50Hz
Pneumatic supply	6 Bar
Weight	300 kg
Hz	50/60 Hz



Ser.Tec. Srl

Via Emilio Salgari 14/d - 31056 Roncade (TV) - Italy
Phone +39 (0)422 798184 - Fax. +39 (0)422 799711
e-mail: sales@ser-tec.org - Website: ser-tec.org



www.facebook.com/sertecsr1



www.instagram.com/sertecgroup



Scan the QR code and visit Rotopress's product page